TECHNICAL DATA SHEET

SCHYDRO-TOP* **Advanced Deep Penetrating Sealer** To Waterproof And Seal Concrete, Pavers, Brick, Block, Stone, Stucco, Grout, Mortar And Manufactured Stone

Use Clear Or With The Wakefield™ Color System For Deep Vibrant Colors That Last.

THE ULTIMATE MASONRY PROTECTOR

HYDRO-TOP is a premium deep penetrating water repellent sealer for many types of porous construction materials such as concrete, pavers, brick, block, stone, stucco, grout, mortar and manufactured stone. HYDRO-TOP works by penetrating deep below the surface and unlike most sealers, does not become slippery when wet. It has a completely natural matte finish and will never flake or peel.

HYDRO-TOP can be used un-tinted as a high performance clear penetrating sealer or with the Wakefield Color System for deep vibrant colors. The entire Wakefield Color System is UV stable, providing unprecedented protection from the sun's damaging effects. The Wakefield color concentrate is suspended directly in the host material. The color at that moment is the color it will stay.

HYDRO-TOP also has the unique ability to be used immediately over the INNERSEAL DPS and INNERSEAL DENSI-DYE systems with no wait time. This two-step application of INNERSEAL DPS or INNERSEAL DENSI-DYE followed by HYDRO-TOP offers the ultimate in protection and is the preferred method for natural and manufactured stone applications. See separate application instructions for INNERSEAL DPS and INNERSEAL DENSI-DYE before using.

Test Specifications: Will meet or exceed:

ASTM E514 - Wind-driven rain resistance, penetration reduction Result: 88.7%
ASTM E514 - Wind-driven rain resistance, Leakage reduction

NOT RECOMMENDED FOR USE ON NON-POROUS MATERIALS SUCH AS POLISHED STONE AND TILE.

MADE IN THE U.S.A. BY:



Murfreesboro, TN 37127

615-566-3065 www.WakefieldMfg.com

DIRECTIONS FOR USE:

Surface Preparation:

- Completely remove all Sealers, oils and contaminates from the concrete or masonry surface. Use only cleaning methods suitable for the substrate you are cleaning.
- Use only the amount of cleaners necessary. Surface and pores must be free of all cleaners before applying HYDRO-TOP.

Application Instructions:

- Allow surface to dry.
- · Mask off all areas not intended to be sealed.
- Add color to desired loading, Up to 100%. Each bottle of color = 25%
- Shake or stir until completely mixed. Keep mixing during application.
- Strain product. Some coagulation is normal due to it's high reactivity.
- Apply with applicator brush, low pressure sprayer or HVLP sprayer.
- Apply liberally, being sure to saturate all areas completely.
- · Do not allow product to puddle.
- Vertical walls apply from bottom up.
- Allow to dry 8 hours for foot traffic and 72 hours for vehicle traffic.

Specifications:

Dilutant Do not dilute Freeze Harm Do not allow to freeze Shelf Life 1 year untinted

Solvent for Clean-up Water

Coverage Rate 120 - 150 sq. ft. / gallon

Detailed Application Instructions, Tech Data Sheets, MSDS, and Color Charts Available at www.WakefieldMfg.com

Manufacturer's Guarantee:

When used as directed, the manufacturer guarantees that HYDRO-TOP will perform as represented. If for some reason you're not satisfied, contact your distributor and the manufacturer will supply you enough HYDRO-TOP for another application. If it is determined that the product was faulty, a refund of the purchase price may be made at the discretion of the distributor.

Safety Information:

CAUTION: KEEP OUT OF REACH OF CHILDREN!

MAY BE HARMFUL IF INHALED. MAY CAUSE SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE DERMATITIS AND BURNS. MAY BE HARMFUL IF SWALLOWED.

Eyes: Wear safety goggles. May cause irritation and redness.

Flush with cool clean water for at least 15 minutes.

If irritation persists, get medical attention.

Skin: Wear appropriate skin protection. May cause irritation and burns.

Wash skin and clothing thoroughly with soap and water. If irritation persists, get medical attention.

Ingestion: May be harmful if swallowed.

Do not eat, drink or smoke during application.

Do not induce vomiting. Get medical attention immediately. Inhalation:

Use only with adequate ventilation or respiratory protection.

May cause respiratory tract irritation. IF INHALED, remove to fresh air. IF NOT BREATHING, give artificial respiration.

Get medical attention immediately.

BEFORE USE, REVIEW MSDS AND SEPARATE APPLICATION INSTRUCTIONS FOR **FURTHER INFORMATION!**